

A COMMUNICATION SYSTEM

BACKGROUND OF THE INVENTION

5 This invention relates to a communication system.

More particularly, the invention relates to a communication system wherein a message is sent in encrypted form over a communication channel.

Communication systems are known wherein so called "symmetric encryption" is used to encrypt the message. In symmetric encryption, the cipher key used to encrypt
10 the message is the same as the cipher key used to decrypt the message. Symmetric encryption has the disadvantage that it is not particularly secure. Firstly, before secure communication using the cipher can take place, it is necessary that the cipher key be communicated to the intended message recipient. Such cipher key communication, if intercepted, renders insecure all subsequent communication using the cipher. Secondly,
15 symmetric encryption is susceptible to analysis of actual messages sent using the cipher, for the purpose of discovering the cipher key. Symmetric encryption has the advantage that it requires relatively low computational power to implement.

Communication systems are known wherein so called public key cryptography is used. In public key cryptography, the cipher key used to encrypt the message is
20 different to the one used to decrypt the message, i.e., the encryption is asymmetric. A prospective message recipient is assigned both the encrypt and decrypt keys of a cipher. The encrypt key is made available to the public, i.e., to anyone wishing to send a message to the recipient, and is termed the public key. The decrypt key is kept secret by the recipient, and is termed the private key. For secure communication to take place, a
25 person wishing to send a message to the recipient, encrypts the message with the recipient's public key, and transmits it to the recipient. The recipient then decrypts the

message using his private key. Thus, in public key cryptography, there is no need for communication by a message sender, of a key required for message decryption. Public key cryptography suffers from the disadvantage that it requires relatively high computational power to implement. Further, if the numbers constituting the public/private keys are not sufficiently large, the encryption is susceptible to analysis of actual messages sent using the cipher, for the purpose of discovering the cipher keys.

A hybrid of symmetric encryption and public key cryptography is known, wherein symmetric encryption is used for message transmission, but prior to message transmission the encrypt/decrypt cipher key is sent using public key cryptography. However, since all messages are sent using symmetric encryption, this hybrid method is still particularly vulnerable to analysis of actual messages sent using the cipher, for the purpose of discovering the cipher key.

SUMMARY OF THE INVENTION

According to a first aspect of the present invention there is provided a communication system comprising: a communication channel; at one end of said channel: (i) a first cipher generator for generating a succession of ciphers, said generator including a first random number generator for generating a sequence of random numbers, each cipher of said succession of ciphers being based on a respective successive portion of said sequence of random numbers; and (ii) a symmetric encryptor for encrypting successive amounts of information for transmission to the other end of said channel, each amount of information being encrypted using a respective one of said succession of ciphers; and, at the other end of said channel: (i) a second cipher generator for generating in synchronism with said first cipher generator the same said succession of ciphers as the first cipher generator, said second cipher generator including a second

random number generator for generating the same said sequence of random numbers as said first random number generator; and (ii) a symmetric decryptor for decrypting the encrypted successive amounts of information received from said one end of said channel, each amount of information being decrypted using the same respective one of
5 said succession of ciphers as was used to encrypt it by said encryptor at said one end of said channel.

Preferably, the system further comprises: at said one end of said channel: (i) means for generating a seed sequence of random numbers, which seed sequence is used by said first random number generator to generate said sequence of random numbers;
10 and (ii) an asymmetric encryptor for encrypting said seed sequence for transmission over said channel to said other end of the channel; and, at said other end, an asymmetric decryptor for decrypting the encrypted seed sequence received from said one end of the channel, said second random number generator using the decrypted seed sequence to generate said same sequence of random numbers as said first random number generator.
15 Suitably, said asymmetric encryptor and said asymmetric decryptor employ public key cryptography.

Preferably, the supply to said symmetric encryptor of each of said successive amounts of information, is signalled to both said first and second cipher generators, whereupon the generators synchronously generate the same next cipher in said
20 succession of ciphers.

Preferably, said symmetric encryptor is a block symmetric encryptor and said symmetric decryptor is a block symmetric decryptor.

Preferably, said first and second cipher generators include: first switching means for receiving said sequence of random numbers; a plurality of subsidiary cipher

Patent 4,306,850

generators, said first switching means switching said successive portions of said sequence of random numbers between said plurality of subsidiary cipher generators, each cipher generated by a subsidiary cipher generator being based on a respective said random number sequence portion switched to it by said first switching means; and
5 second switching means for switching in turn between said subsidiary cipher generators to provide said succession of ciphers.

Preferably, in a system according to the previous paragraph, said plurality of subsidiary cipher generators is two subsidiary cipher generators, and said first and second switching means switch simultaneously but to different ones of said two
10 subsidiary cipher generators.

Preferably, in a system according to the previous paragraph, or the previous paragraph but one, each said subsidiary cipher generator comprises: third switching means; a plurality of exclusive OR (XOR) gates, said third switching means switching random numbers received by the subsidiary cipher generator between said plurality of
15 XOR gates; and a plurality of registers, one in respect of each XOR gate, each register both receiving the output of, and providing a further input to, its respective XOR gate, the contents of said plurality of registers constituting the cipher generated by the subsidiary cipher generator.

According to a second aspect of the present invention there is provided a
20 communication method comprising the steps of: at one end of a communication channel: (i) generating a first sequence of random numbers; (ii) generating a succession of ciphers, each cipher being based on a respective successive portion of said first sequence of random numbers; and (iii) symmetrically encrypting successive amounts of information for transmission to the other end of said channel, each amount of

information being encrypted using a respective one of said succession of ciphers; and, at the other end of said channel: (i) generating the same said first sequence of random numbers; (ii) in synchronism with the generation of said succession of ciphers at said one end of said channel (31), generating the same said succession of ciphers at said
5 other end of the channel (31); and (iii) symmetrically decrypting the encrypted successive amounts of information received from said one end of said channel, each amount of information being decrypted using the same respective one of said succession of ciphers as was used to encrypt it at said one end of said channel.

Preferably, said method further comprises the steps of: at said one end of said
10 channel: (i) generating a seed sequence of random numbers, which seed sequence is used to generate said first sequence of random numbers; and (ii) asymmetrically encrypting said seed sequence for transmission to said other end of said channel; and, at said other end, asymmetrically decrypting the encrypted seed sequence received from said one end of the channel, the decrypted seed sequence being used to generate said
15 same said first sequence of random numbers. Suitably, said asymmetric encryption and said asymmetric decryption employ public key cryptography.

Preferably, in said method, the supply for symmetric encryption of each of said successive amounts of information, is signalled, whereupon there is the synchronous generation at each end of said channel of the same next cipher in said succession of
20 ciphers.

Preferably, in said method, said symmetric encryption is block symmetric encryption and said symmetric decryption is block symmetric decryption.

According to a third aspect of the present invention there is provided a cipher generator for generating a succession of ciphers, said generator comprising: a random

number generator for generating a sequence of random numbers; first switching means for receiving said sequence of random numbers; a plurality of subsidiary cipher generators, said first switching means switching successive portions of said sequence of random numbers between said plurality of subsidiary cipher generators, each cipher
5 generated by a subsidiary cipher generator being based on a respective said random number sequence portion switched to it by said first switching means; and second switching means for switching in turn between said subsidiary cipher generators to provide said succession of ciphers.

Preferably, in said generator, said plurality of subsidiary cipher generators is two
10 subsidiary cipher generators, and said first and second switching means switch simultaneously but to different ones of said two subsidiary cipher generators.

Preferably, in said generator, each said subsidiary cipher generator comprises:
third switching means; a plurality of exclusive OR (XOR) gates, said third switching means switching random numbers received by the subsidiary cipher generator between
15 said plurality of XOR gates; and a plurality of registers, one in respect of each XOR gate, each register both receiving the output of, and providing a further input to, its respective XOR gate, the contents of said plurality of registers constituting the cipher generated by the subsidiary cipher generator.

BRIEF DESCRIPTION OF THE DRAWINGS

20 A communication system in accordance with the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a block schematic diagram of the system;

Figure 2 is a schematic circuit diagram of first/second cipher generators of the system of Figure 1; and

Operating in analogous manner to bus selector 11, each bus selector 13, 15 cycles the random numbers it receives around its four outputs, supplying each received number to the next of its four outputs. Each bus selector 13, 15 does this by indexing the count of its respective register 19, 21, which registers count only one increment before causing switching. Thus, the following outputs R4-R11 of bus selectors 13, 15 will be produced in response the above example sequence of R2/R3s: R4 = 100, 12, 44; R5 = 50, 18, 35; R6 = 30, 56, 42; R7 = 80, 78, 99; R8 = 90, 34; R9 = 60, 11; R10 = 40, 23; and R11 = 20, 54.

Each of outputs R4-R11 is supplied to a respective exclusive-OR (XOR) gate 23, each of which gates in turn supplies a respective register 25. Each output R4-R11 forms one input to its respective XOR gate 23. The other input to each gate 23 is formed

5 Outputs R12-R19 are supplied to 8:4 indexed bus selector 27. Register 17, in addition to controlling the switching of bus selector 11, also controls the switching of bus selector 27, which selects its four outputs C1-C4 by switching between set of four inputs R12-R15 and set of four inputs R16-R19. Register 17, when switching bus selector 11 to supply bus selector 13, simultaneously switches bus selector 27 to pass R16-R19 to C1-C4. Similarly, register 17, when switching bus selector 11 to supply bus selector 15, simultaneously switches bus selector 27 to pass R12-R15 to C1-C4. In this manner, whilst a current C1-C4 are present as outputs of bus selector 27, the next C1-C4 are being created, i.e., creation of the next C1-C4 occurs in parallel with the current C1-C4. C1-C4 constitute the output of first cipher generator 3. 1:4 cyclic bus selector 13, register 19, and the XOR gates 23 and registers 25 supplied by bus selector 13, together, can be considered a subsidiary cipher generator of cipher generator 3. The same applies in respect of 1:4 cyclic bus selector 15, register 21, and the XOR gates 23 and registers 25 supplied by bus selector 15. Bus selectors 11, 27 switch between these two subsidiary ciphers generators, bus selector 11 switching to supply one, while bus selector 27 switches to take the output of the other. Since, in this example, R12-R15 are currently being created (see above mentioned outputs R4-R11, R4-R7 each have one more number than R8-R11) the current C1-C4 comprise R16-R19, i.e., C1 = 120, C2 = 55, C3 = 63 and C4 = 20.

Returning to the output Sp of PRNG 1, this is also supplied to public key encryptor 29, which utilizes the known RSA (Rivest-Shamir-Adleman) cipher to encrypt Sp . In this example, the public key/private key pair of the RSA cipher is described by $e = 3$, $n = 33$ and $d = 7$, where e and n together form the public key, and d is the private key. Thus, each value of $Sp = 5, 3, 1, 5, 1$ is encrypted using the equation $Se = Sp^e \bmod n$, to give $Se = 26, 27, 1, 26, 1$. The output Se of encryptor 29 is transmitted via communication channel 31 to public key decryptor 33, where it is decrypted using the equation $Sp = Se^d \bmod n$, to recreate $Sp = 5, 3, 1, 5, 1$. The output Sp of decryptor 33 is supplied to second cipher generator 35. The circuitry of second cipher generator 35 is precisely the same as first cipher generator 3 shown in Figure 2. Sp is used by second cipher generator 35 in precisely analogous manner to first cipher generator 3 to generate the same $C1-C4$, i.e., $C1 = 120$, $C2 = 55$, $C3 = 63$ and $C4 = 20$.

This completes initialization of the communication system. Sending of the message $Mp = 65$ will now be described.

Supply of the message Mp for transmission, is signalled to both first and second cipher generators 3, 35 by a pulse $Co1$ (no signal Sp is used in transmission of Mp , signal Sp is only used in system initialization). The following then occurs in both cipher generators 3, 35. In response to pulse $Co1$, pulse series generator 9 supplies four pulses to PRNG 5, which in turn generates four random numbers $R1 = 87, 71, 8, 200$. Register 17 switches bus selector 11 to copy $R1$ to $R3$, to supply bus selector 15. This occurs because the last four numbers (44, 35, 42, 99) routed by bus selector 11 were copied to $R2$, to supply bus selector 13. Register 17, at the same time as switching bus selector 11, switches 8:4 indexed bus selector 27. Hence, bus selector 27 now copies $R12-R15$ to

C1-C4 in place of R16-R19. Thus, now, in respect of both cipher generators, $C1 = 68$, $C2 = 3$, $C3 = 12$ and $C4 = 125$.

The message M_p itself is supplied to block symmetric encryptor 37, where it is encrypted using C1-C4 received from cipher generator 3, as will now be explained.

5 Referring also to Figure 3, M_p is supplied to an input of each AND gate 39, 41. The other input to gate 39, $N_{low} = 0000000011111111$ (255). The other input to gate 41, $N_{high} = 1111111100000000$ (65280). The function of gates 39, 41 is to extract the first and second 8 bit characters respectively of each two character message block (see above). Now, M_p is transmitted as 0000000001000001, therefore the output M_{low} of
10 AND gate 39 will be 0000000001000001 (i.e. $M_p = 65$), and the output M_{high} of AND gate 41 will be 0000000000000000 (since M_p is a one character message).

Shift register 43 shifts M_{high} to the right by 8 bits to create $SM_{high} = 0000000000000000$, which is supplied to one input of XOR gate 45. M_{low} is supplied to both MOD 4 circuit 47 and one input of XOR gate 49. MOD 4 circuit 47 computes
15 $MM_{low} = M_{low} \bmod 4 = 1$, and supplies this to 4:1 indexed bus selector 51. Bus selector 51 is also supplied with the output C1-C4 (68, 3, 12, 125) of first cipher generator 3. Bus selector 51 uses MM_{low} to select one of C1-C4. In this regard, it is to be appreciated that MM_{low} will always be one of 0, 1, 2 or 3. $MM_{low} = 0$ causes bus selector 51 to select C1, 1 selects C2, 2 selects C3, and 3 selects C4. $C2 = 3$ is therefore
20 selected, and supplied as signal E1 to the other input of XOR gate 45.

XOR gate 45 XORs together $SM_{high} = 0$ and $E1 = 3$ to provide output $P1 = 3$, which is supplied to both one input of OR gate 53 and MOD 4 circuit 55. MOD 4 circuit 55 computes $MP1 = P1 \bmod 4 = 3$, and supplies this to 4:1 indexed bus selector 57. The operation of bus selector 57 is precisely analogous to that of bus selector 51. Hence, C4

10

15

20

encryption is used for actual message transmission, the cipher key is new for every message sent. There is therefore only a relatively small amount of transmission using any given cipher key, thereby severely frustrating analysis of actual messages sent for the purpose of cipher key discovery. In addition, provided the pseudo random number
5 generated by generator 5 is sufficiently complex, knowledge of the cipher key used for the transmission of one message, does not enable analysis to determine this pseudo random number, and hence the cipher keys for other messages sent.

Further, each message's cipher key is never transmitted. The cipher keys are generated independently and in synchronism at each end of the communication channel.
10 This is achieved by the initial transmission, by secure public key cryptography, of a random number generating seed, which seed is then used in corresponding manner at each end of the communication channel to synchronously generate the message specific cipher keys. The one time sending of a random number generating seed by public key cryptography, does not provide a sufficient quantity of transmission to enable analysis
15 of actual transmission, for the purpose of discovering the private decrypt key of the public key cryptography (and hence the random number generating seed). This is so even in the case where the numbers constituting the public/private keys are relatively small.

Further, relatively low power is required for implementation of the present
20 invention, since symmetric encryption is used for all encryption apart from the one time encryption of the random number generating seed.

In the communication system described above by way of example, there is an encryptor 37 at the transmit end of the of the communication channel, and a decryptor
61 at the receive end. It is to be appreciated that, since the circuitry of these two

09989374230
10101112131415161718192021222324252627282930313233343536373839404142434445464748495051525354555657585960616263646566676869707172737475767778798081828384858687888990919293949596979899

Parameter	Value	Unit
Temperature	25.0	°C
Pressure	1.0	atm
Concentration	0.1	M
pH	7.0	
Wavelength	400	nm
Time	10	min
Distance	10	cm
Volume	10	ml
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	J
Power	10	W
Frequency	10	Hz
Wavenumber	10	cm ⁻¹
Angle	10	°
Area	10	cm ²
Volume	10	cm ³
Mass	10	g
Energy	10	